

Counterbalanced

4-wheel engine trucks torque converter

imd
isd



M 315 - 318 Stage V	15 t - 18 t
	6970 mm
	DIESEL / LPG

imd
isd



M 320 - 325 Stage V	20 t - 25 t
	6970 mm
	DIESEL / LPG

imd
isd



M 330 - 335 Stage V	3.0 t - 3.5 t
	6970 mm
	DIESEL / LPG

4-wheel engine trucks hydrostatic

imd
isd



M 315H - 318H Stage V	15 t - 18 t
	6970 mm
	LPG version only

imd
isd



M 320H - 325H Stage V	20 t - 25 t
	6970 mm
	DIESEL / LPG

imd
isd



M 330H - 335H Stage V	3.0 t - 3.5 t
	6970 mm
	DIESEL / LPG

LEGEND

	Rated Lift / Load capacity		Maximum battery
	Rated towing capacity		Fuel type
	Maximum lifting height		Additional info

3-wheel electric trucks

imd
isd



B
210 - 213
- 215

KG	10 t - 125 t - 15 t
↑	6500 mm
🔋	24V / 875 Ah

imd
isd



B
315 - 316(L)
318(L) - 320

KG	15 t - 16 t - 18 t - 20 t
↑	7500 mm
🔋	48V / 750 Ah

4-wheel electric trucks

imd
isd



B
416(L) - 418L
- 420(L)

KG	16 t - 18 t - 20 t
↑	7500 mm
🔋	48V / 750 Ah

imd
isd



B
620 - 625(L-HL)
630(L-HL) - 635

KG	20 t - 25 t - 30 t - 35 t
↑	6500 mm
🔋	80V / 775 Ah

imd



B
640 - 645
- 650

KG	4.0 t - 4.5 t 5.0 t
↑	6500 mm
🔋	80V / 930 Ah

Heavy-duty electric trucks

isd



B
860 - 870
- 880(H)

KG	6.0 t - 7.0 t - 8.0 t
↑	7000 mm
🔋	80V / 1240 Ah

Warehouse equipment

Hand pallet trucks



CE 200 - 230 - 300	20 t - 23 t - 30 t
	The 23 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 20 t model.



CE 200st	20 t
	Stainless steel version.



H 210 - 210E	1.0 t
	800 mm
	Available with manual and electric lift.

Powered pallet trucks



P 013i	1.3 t
	Li-Ion 24V / 36 Ah
	Available with fast charger for 2½ hour charging time.



P 113	1.3 t
	24V / 63 Ah
	Integrated batteries and charger.



P 214 - 216 - 218 - 220 - 225	1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t
	24V / 300 Ah
	Optional operator platform available for P220.

Li-ION



P 216i	1.6 t
	Li-Ion 24V / 150 Ah
	Available with internal or external charger.



P 320 - 322	2.0 t - 2.2 t
	24V / 600 Ah
	Available with a choice of travel speed (6,8,10 km/h).

Reach trucks



R 112 - 114 - 116	1.2 t - 1.4 t - 1.6 t
	8500 mm
	48V / 620 Ah
	Also available as a drive-in version with narrow overhead guard.

imd
INDUSTRIAL MACHINERY DESIGN



R 214 - 216	1.4 t - 1.6 t
	10000 mm
	48V / 620 Ah
	Also available as a cold store version as well as drive-in version with narrow overhead guard.

imd
INDUSTRIAL MACHINERY DESIGN



R 314 - 316 - 318 - 320 - 325	1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t
	13000 mm
	48V / 930 Ah
	Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard.

Powered stacker trucks



S 010i	10 t
	3600 mm
	Li-ion 24V / 60 Ah
	Integrated battery and charger. Lift heights 2.9 and 3.6 m.



S 110 - 110S	10 t
	1960 mm
	24V / 63 Ah
	Integrated batteries and charger. 3100; straddle support arm variant.



S 210 - 212 - 214	10 t - 12 t - 14 t
	4755 mm
	24V / 300 Ah
	Optional operator platform available.



S 215 - 216 - 220	145 t - 16 t - 20 t
	6000 mm
	24V / 500 Ah
	Available with a choice of chassis width.



S 208L	0,8 t
	1580 mm
	24V / 230 Ah
	Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment.



S 212L - 214L	12 t - 14 t
	4755 mm
	24V / 300 Ah
	Elevating support arms. Optional operator platform available.



S 215L - 216L - 220L	145 t - 16 t - 20 t
	6000 mm
	24V / 500 Ah
	Elevating support arms.



S 220D	10 t
	2100 mm
	24V / 300 Ah
	Double stacked lift: 600 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. Optional operator platform available.



S 212S	1,2 t
	4755 mm
	24V / 300 Ah
	Straddle support arms. Optional operator platform also available.



S 214S	14 t
	5400 mm
	24V / 300 Ah
	Straddle support arms variant.



S 312 - 314 316 - 320	12 t - 14 t - 16 t - 20 t
	6000 mm
	24V / 300 Ah
	Available with a choice of speeds up to 10km/h.



S 312L - 314L - 316L - 320L	12 t - 14 t - 16 t - 20 t
	6000 mm
	24V / 500 Ah
	Elevating support arms. Available with a choice of speed, up to 10km/h.







S 314S	14 t
	5350 mm
	24V / 500 Ah
	Straddle support arms.





Warehouse equipment

Low Level Order Pickers







125 - 125P	 2.5 t
	 235mm
	 24V / 620 Ah
	 The lifting platform version allows the driver to pick goods up to 2700 mm







112 - 112P	 12 t
	 800mm
	 24V / 620 Ah
	 The lifting platform version allows the driver to pick goods up to 2700 mm



120X - 118XP	 20 t / XP1.8 t
	 800mm
	 24V / 620 Ah
	 The lifting platform version allows the driver to pick goods up to 2700 mm



110 - 110W	 10 t
	 O110 - 1880mm O110W - 1100 mm
	 24V / 620 Ah
	 Low step height 180 mm W version without barrier for handling bulky goods



112CB	 12 t
	 4150mm
	 24V / 620 Ah
	 2-in-1 solution, O112CB can be used for picking as well as stacking

Towing solutions

3-Wheel Tow Tractors



TTE 40	↔	4.0 t
	KG	---
	Battery	24V / 360 Ah
	i	Drum brakes on all wheels. Activa comfort seat



TTE 71	↔	7.0 t
	KG	---
	Battery	24V / 360 Ah
	i	Double circuit drum brakes on all wheels. Full light kit

4-Wheel Tow Tractors



TE 80	↔	8.0 t
	KG	0.1 t
	Battery	48V / 375 Ah
	i	Double circuit drum brakes on all wheels. Full LED light kit



TE 80IXB	↔	8.0 t
	KG	0.1 t
	Battery	48V / 375 Ah
	i	Double circuit drum brakes on all wheels. 2 nd seat possible



TE 152	↔	15.0 t
	KG	0.2 t
	Battery	48V / 625 Ah
	i	Disk brakes on all 4 wheels. Grammer seats for driver and passenger



TE 252	↔	25.0 t
	KG	0.2 t
	Battery	80V / 620 Ah
	i	Disk brakes on all 4 wheels. Grammer seats for driver and passenger



TE 293	↔	29.0 t
	KG	0.2 t
	Battery	80V / 620 Ah
	i	Disk brakes on all 4 wheels. Grammer seats for driver and passenger



TE 301	↔	30.0 t
	KG	0.1 t
	Battery	80V / 620 Ah
	i	Disk brakes on all 4 wheels. Grammer seats for driver and passenger



TE 501	↔	50.0 t
	KG	0.2 t
	Battery	80V / 930 Ah
	i	Disk brakes on all 4 wheels. Grammer seats for driver and passenger

Platform Trucks



PE 15.1	KG	15 t
	↔	10.0 t
	Battery	48V / 500 Ah
	i	Oil cooled disk brakes on rear wheels. 2 nd seat as option



PE 20.1	KG	20 t
	↔	10.0 t
	Battery	48V / 480 Ah
	i	Oil cooled disk brakes on rear wheels. 2 nd seat is standard

IMD Intelligent Mast Design

IMD (Intelligent Mast Design) is a pioneering concept designed and engineered exclusively within the CESAB Group.

We believe that the mast is key to safe and productive materials handling. We use 3-D computer modelling, Finite Element Model analysis with a computerised simulation to find the best design solution for our masts.

Thanks to IMD, CESAB provides you with the industry leading levels of visibility and performance.

Among other advantages of the Intelligent Mast Design:

- High strength and rigidity
- Low maintenance
- Low energy usage
- Superior forward visibility
- Smooth operation
- More durability
- Productivity



By applying the IMD concept to the design of each individual truck, CESAB has created a range of forklifts that provide you outstanding performance.